


# CXG2.5



**connectwell**  
THE RIGHT CONNECTION

## 2.5 sq.mm Ground/Earth Spring Clamp Terminal Blocks

These Terminal Blocks have specially designed alloy feet which help in achieving very low contact resistance and vibration proof grounding with the DIN rails. They green/yellow colour coded as industry standards.

THIS PRODUCT IS NOT FOR SALE IN GERMANY

### TECHNICAL DATA

Housing Material	Polymide
Product Function	Earthing/Grounding
Mounting Possibility	DIN 35/DIN 35-15 Rail
Operated by	Screw Driver
Pollution Degree	3

### CONNECTION DATA

Conductor Cross Section Stranded min.	0.2 mm <sup>2</sup>
Conductor Cross Section Stranded max.	2.5 mm <sup>2</sup>
Conductor Cross Section AWG/Kcmil min	24 AWG
Conductor Cross Section AWG/Kcmil max	12 AWG
Conductor Cross Section Stranded with Ferrule/Lug min	0.2 mm <sup>2</sup>
Conductor Cross Section Stranded with Ferrule/Lug max	2.5 mm <sup>2</sup>
2 Conductors with same Cross Section Stranded min	0.2 mm <sup>2</sup>
2 Conductor with same Cross Section Stranded max	1 mm <sup>2</sup>
Conductor Cross Section Solid min	0.2 mm <sup>2</sup>
Conductor Cross Section Solid max	4 mm <sup>2</sup>
Stripping Length	10 mm

### DIMENSIONS

Height with DIN 35 x 15 mm rail	45.2 mm
Height with DIN 35 x 7.5 mm rail	37.6 mm
Length	49.7 mm
Width (Thickness)	5 mm

### ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CXG2.5	2.5 sq.mm Ground/Earth Spring Clamp Terminal Blocks	100

### ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50

### ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50

	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50

	CA103	End Clamp in Polyamide suitable for Din 35/Din 35-15 rails	50
--	-------	------------------------------------------------------------	----

	CA702	End Clamp in Polyamide 66 suitable for Din 32 / Din 35 / Din 35-15 Rails	50
--	-------	--------------------------------------------------------------------------	----

	CA802	End Clamp in Polyamide suitable for Din 35 / Din 35-15 Rails	50
--	-------	--------------------------------------------------------------	----

	EPCX2.5	End Plate in Grey Colour	50
	EPCX2.5BU	End Plate in Blue Colour	50


	PPCX4	Partition Plate in Grey colour	50
--	-------	--------------------------------	----

	JX2.5/2	Shorting Link for 2.5 sq mm series	100
	JX2.5/3	Shorting Link for 2.5 sq mm series	50
	JX2.5/4	Shorting Link for 2.5 sq mm series	50
	JX2.5/5	Shorting Link for 2.5 sq mm series	50
	JX2.5/6	Shorting Link for 2.5 sq mm series	50
	JX2.5/7	Shorting Link for 2.5 sq mm series	10
	JX2.5/8	Shorting Link for 2.5 sq mm series	10
	JX2.5/10	Shorting Link for 2.5 sq mm series	10

	CA509/K5	Blank Marking Tag	100
--	----------	-------------------	-----


	WLX2.5	Warning label suitable for 5mm wide terminal block	50
--	--------	----------------------------------------------------	----

CXG2.5



**connectwell**  
THE RIGHT CONNECTION

**ACCESSORIES**

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	JXS10/2.5	Step Down Shorting Link for CX series	10
C:\inetpub\wwwroot\Connectwell.Website\	JXS6/2.5	Step Down Shorting Link for CX series	10

**APPROVALS**



**NOTES**

THIS PRODUCT IS NOT FOR SALE IN GERMANY

**RATINGS AS PER STANDARDS**

STANDARDS	UL 1059	CSA C.22.2 No:158	IEC/EN60947-7-1
Approvals	UL	CSA	CE
Conductor Cross Section Stranded min.	24 AWG	24 AWG	0.2 mm <sup>2</sup>
Conductor Cross Section Stranded max.	12 AWG	12 AWG	2.5 mm <sup>2</sup>